


Analytical balance KERN ABS-N · ABJ-NM · ACS · ACJ



**KERN ACS/ACJ** with standard data interface RS-232 and USB

The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]

### Features

- **ABJ-NM: Automatic internal adjustment** in the case of a change in temperature  $\geq 2$  °C or timecontrolled every 4 h, guarantees high degree of accuracy and makes the balance independent of its location of use
- **ABS-N: Adjusting program CAL** for quick setting of the balance accuracy using an external test weight
- **ACS** identical to ABS-N, **ACJ** identical to KERN ABJ-NM, but with RS-232 and USB data interface integrated as standard
- **Dosage aid:** High-stability mode and other filter settings can be selected
- **Simple recipe weighing and documenting** with a combined tare/print function. In addition, the ingredients for the recipe are numbered automatically and printed out with their corresponding number and nominal weight
- **Automatic data output to the PC/printer** each time the balance is steady
- **Identification number:** 4 digits, printed on calibration protocol freely programmable
- ABJ-NM, ACJ have OIML certification
- **Protective working cover** included with delivery

Analytical balance KERN ABS-N · ABJ-NM · ACS · ACJ



## Technical data

- Large LCD display, digit height 14 mm
- Dimensions weighing surface, stainless steel,  $\varnothing$  91 mm
- Overall dimensions (incl. draught shield) W×D×H 210×340×325 mm
- Weighing space W×D×H 174×162×227 mm
- Net weight approx. 6 kg
- Permissible ambient temperature 10 °C/30 °C

## Accessories

- **Protective working cover**, scope of delivery: 5 items, KERN ACS-A02S05
- **1 Set for density determination** of liquids and solids with density  $\leq/\geq$  1, the density is indicated directly on the display, KERN YDB-03
- **2 Ionizer** to neutralise electrostatic charge, KERN YBI-01A
- **KERN ABS-N/ABJ-NM: Data interface RS-232**, interface cable included, approx. 1,5 m KERN ACS-A01
- **3 Weighing table** to absorb vibrations and oscillations, which would otherwise distort the weighing result, KERN YPS-03
- **Minimum weight of sample**, smallest weight to be weighed, depending on the required process accuracy, only in combination with a DAkkS calibration certificate, KERN 969-103
- Further details, plenty of further accessories and suitable printers see *Accessories*




Single-cell advanced technology:

- **Fully automatic manufactured weighing cell from one piece of material**
- **Stable temperature behaviour**
- **Short stabilisation time:** steady weight values within approx. 3 s under laboratory conditions
- **Shock proof construction**
- **High corner load performance**

## STANDARD



## OPTION

































## FACTORY



Model	Weighing capacity [Max] g	Readability [d] mg	Verification value [e] mg	Minimal load [Min] mg	Reproducibility mg	Linearity mg	Option		
							Verification	DAkkS Calibr. Certificate	
KERN							MT KERN	DAkkS KERN	
ABS 80-4N	82	0,1	-	-	0,2	± 0,3	-	963-101	
ABS 120-4N	120	0,1	-	-	0,2	± 0,3	-	963-101	
ABS 220-4N	220	0,1	-	-	0,2	± 0,3	-	963-101	
ABS 320-4N	320	0,1	-	-	0,2	± 0,3	-	963-101	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.									
ABJ 80-4NM	82	0,1	1	10	0,2	± 0,3	965-201	963-101	
ABJ 120-4NM	120	0,1	1	10	0,2	± 0,3	965-201	963-101	
ABJ 220-4NM	220	0,1	1	10	0,2	± 0,3	965-201	963-101	
ABJ 320-4NM	320	0,1	1	10	0,2	± 0,3	965-201	963-101	
ACS 80-4	NEW 82	0,1	-	-	0,2	+/- 0,3	-	963-101	
ACS 100-4	NEW 120	0,1	-	-	0,2	+/- 0,3	-	963-101	
ACS 200-4	NEW 220	0,1	-	-	0,2	+/- 0,3	-	963-101	
ACS 300-4	NEW 320	0,1	-	-	0,2	+/- 0,3	-	963-101	
ACJ 80-4M	NEW 82	0,1	1	10	0,2	+/- 0,3	965-201	963-101	
ACJ 100-4M	NEW 120	0,1	1	10	0,2	+/- 0,3	965-201	963-101	
ACJ 200-4M	NEW 220	0,1	1	10	0,2	+/- 0,3	965-201	963-101	
ACJ 300-4M	NEW 320	0,1	1	10	0,2	+/- 0,3	965-201	963-101	

NEW New model

## Pictograms

 <b>Internal adjusting:</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 <b>KERN Communication Protocol (KCP):</b> It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	 <b>Protection against dust and water splashes IPxx:</b> The type of protection is shown in the pictogram.
 <b>Adjusting program CAL:</b> For quick setting up of the balance's accuracy. External adjusting weight required	 <b>GLP/ISO log:</b> The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	 <b>Stainless steel:</b> The balance is protected against corrosion
 <b>Easy Touch:</b> Suitable for the connection, data transmission and control through PC, tablet or smartphone	 <b>GLP/ISO log:</b> With weight, date and time. Only with KERN printers	 <b>Suspended weighing:</b> Load support with hook on the underside of the balance
 <b>Memory:</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 <b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device
 <b>Alibi memory:</b> Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 <b>Recipe level A:</b> The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 <b>Rechargeable battery pack:</b> Rechargeable set
 <b>Data interface RS-232:</b> To connect the balance to a printer, PC or network	 <b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 <b>Universal mains adapter:</b> with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
 <b>RS-485 data interface:</b> To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 <b>Recipe level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition	 <b>Mains adapter:</b> 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
 <b>USB data interface:</b> To connect the balance to a printer, PC or other peripherals	 <b>Totalising level A:</b> The weights of similar items can be added together and the total can be printed out	 <b>Power supply:</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 <b>Bluetooth* data interface:</b> To transfer data from the balance to a printer, PC or other peripherals	 <b>Percentage determination:</b> Determining the deviation in % from the target value (100 %)	 <b>Weighing principle: Strain gauges</b> Electrical resistor on an elastic deforming body
 <b>WLAN data interface:</b> To transfer data from the balance to a printer, PC or other peripherals	 <b>Weighing units:</b> Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details	 <b>Weighing principle: Tuning fork</b> A resonating body is electromagnetically excited, causing it to oscillate
 <b>Control outputs (optocoupler, digital I/O):</b> To connect relays, signal lamps, valves, etc.	 <b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements	 <b>Weighing principle: Electromagnetic force compensation</b> Coil inside a permanent magnet. For the most accurate weighings
 <b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements	 <b>Interface for second balance:</b> For direct connection of a second balance	 <b>Weighing principle: Single cell technology:</b> Advanced version of the force compensation principle with the highest level of precision
 <b>Interface for second balance:</b> For direct connection of a second balance	 <b>Network interface:</b> For connecting the scale to an Ethernet network	 <b>Verification possible:</b> The time required for verification is specified in the pictogram
 <b>Network interface:</b> For connecting the scale to an Ethernet network	 <b>Weighing with tolerance range:</b> (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 <b>DAKkS calibration possible:</b> The time required for DAKkS calibration is shown in days in the pictogram
 <b>Wireless data transfer:</b> between the weighing unit and the evaluation unit using an integrated radio module	 <b>Hold function:</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram
<small>*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN &amp; SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.</small>	 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram	

## KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

## Your KERN specialist dealer: